

Technical Data Sheet

Issue date: 08/01/2008 Date last modification: 13/12/2016

4-SL1D-01982 COLOUR BLUE AP904 WK85 SPL

Face Material

Blue coloured woodfree paper.

Type Coated paper

Colour and Finish Blue

ISO-536 Weight 80 g/m² ±10% ISO 534-80 Thickness 78 µ ±10%

OFFSET SHEETS - LOGISTIC

Adhesive

Acrylic permanent adhesive. Good adhesion on a wide variety of materials including apolar substrates (like PE and

Reference AP904

Acrylic permanent Type

Min. Appl. Temp. +5°C

-40°C/+100°C Service Temp. Shear Medium

13 N/25mm FINAT FTM9 Tack Final Adhesion 11 N/25mm FINAT FTM2

This adhesive is approved by ISEGA (Direct contact dry & moist, non fatty foodstuffs) according to the German Recommendations XIV and complies with FDA 175.105.

Liner

One side siliconised clay coated Type

Kraft

Colour and Finish White

PP-032 - ISO 536 85 g/m² ±10% Weight

ISO 534 **Thickness** 87 µ ±10% DIN 53 147-64 Transparency n.a. %

Applications

General and promotional labels.

Printing Methods

Printable with letterpress UV, screenprinting UV and flexo

Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of $22^{\circ}C \pm 2^{\circ}C$ and 50 \pm 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.



