

GRAPHICS - RI-MARK

Issue date : 06/12/2013
Date last modification : 06/04/2017**4-GL2C-07654 APPLICATION TAPE CLEAR 150 MY****Face Material**

Gloss clear polyethylene.

Type	Polyethylene	
Colour and Finish	Gloss clear	
Weight	140 g/m ² ±10%	ISO-536
Thickness	150 μ ±10%	ISO 534-80

Adhesive

Acrylic removable.

Reference	AR	
Type	Acrylic removable	
Min. Appl. Temp.	+5°C	
Service Temp.	-40°C/+120°C	
Shear	High	
Tack	2 N/25mm	FINAT FTM9
Final Adhesion	2 N/25mm	FINAT FTM2

Applications

The use of film Application Tape is recommended for assembling multi-colored graphics.

Printing MethodsAs a rule it is not printable.
Testing for suitability between media, printers and inks is always recommended prior to use.**Shelf life**24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.
All information is subject to change without prior notice.