

OFFSET SHEETS - PROMOTIONAL

Issue date : 05/01/2005
Date last modification : 06/12/2018

4-SL1B-10827 - SEMIGLOSS AP904 WK85 RIT/GRY SPL38 FSC® CERTIFIED
Face Material

Medium gloss white coated woodfree paper.FSC® certified.

Type	Coated paper
Colour and Finish	White
Weight	80 g/m ² ±10% ISO-536
Thickness	65 µ ±10% ISO 534-80

Adhesive

Acrylic permanent adhesive. Good adhesion on a wide variety of materials including apolar substrates (like PE and PP).

Reference	AP904
Type	Acrylic permanent
Min. Appl. Temp.	+5°C
Service Temp.	-40°C/+100°C
Shear	Medium
Tack	13 N/25mm FINAT FTM9
Final Adhesion	10 N/25mm FINAT FTM2

This adhesive is approved by ISEGA (Direct contact dry & moist, non fatty foodstuffs) according to the German Recommendations XIV and complies with FDA 175.105.

Liner

Type	One side siliconised clay coated Kraft
Colour and Finish	White
Weight	85 g/m ² ±10% PP-032 - ISO 536
Thickness	87 µ ±10% ISO 534

Applications

General and promotional labels, where a semi-gloss finish is required.

Printing Methods

Printable with letterpress UV, flexo UV and laser. Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.