

Technical Data Sheet

Issue date: 18/05/2011 Date last modification: 13/12/2016

# **GRAPHICS** - Uncoated Papers

# 4-GL3B-04973 RI-213 GLOSS SILVER ASP26 PERMANENT WK120

### Face Material

Gloss silver metallised rigid vinyl.

Type Rigid vinyl Colour and Finish Gloss silver

# **Adhesive**

Solvent based acrylic permanent adhesive featuring high cohesion and good water resistance. Designed for a wide variety of substrates such as glass, ABS, PS, PVC. Unsuitable for apolar surfaces (like PE and PP).

Reference ASP26 permanent Type Acrylic permanent

Min. Appl. Temp. +10°C

Service Temp. -20°C/+130°C

Shear High

Tack Medium N/inch² Final Adhesion High N/inch

#### Liner

Type One side siliconised clay coated

Kraft

Colour and Finish White

Weight 120 g/m<sup>2</sup> PP-032 - ISO

±10% 536

Thickness 108  $\mu$  ±10% ISO 534 Transparency n.a. % DIN 53 147-64

# **Applications**

Advertising specialties, high quality metallic decorations and promotional labels.

### **Printing Methods**

Printable in UV and solvent based screenprinting and offset UV.

Testing for suitability between media, printers and inks is always recommended prior to use.

# Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.

All information is subject to change without prior notice.



