

Technical Data Sheet

OFFSET SHEETS - PROMOTIONAL

4-SL1F-01841 GLOSS GOLD AP904 WK85

Face Material

Laminated of white paper and bright gold aluminium foil, top coated.

Type Colour and Finish Weight Thickness Paper laminated with aluminiumGloss gold72 g/m² $\pm 10\%$ ISO-53667 µ $\pm 10\%$ ISO 534-80

Adhesive

Permanent acrylic adhesive for general purposes.

Reference Type Min. Appl. Temp. Service Temp. Shear Tack Final Adhesion

AP904 Acrylic permanent +5°C -40°C/+100°C Medium 13 N/25mm FINAT FTM9 11 N/25mm FINAT FTM2

Liner

TypeOne side siliconised clay coated
KraftColour and FinishWhiteWeight $85 \text{ g/m}^2 \pm 10\%$ PP-032 - ISO 536Thickness $87 \ \mu \pm 10\%$ ISO 534Transparencyn.a. %DIN 53 147-64

Issue date : 04/11/2010 Date last modification : 13/12/2016

Applications

General and promotional labels.

Printing Methods

Printable with letterpress UV, flexo UV, offset UV and gravure. Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of $\ 22^\circ C \ \pm \ 2^\circ C$ and 50 $\pm \ 5\%$ of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.



Ritrama S.p.A. Via Senatore Simonetta, 24 20867 Caponago (MB) ITALN e-mail:info@ritrama.com w w w . r i t r a m a . c o m

