

Technical Data Sheet

Issue date: 08/09/2010

Date last modification: 02/09/2019

ROLL LABEL - WINE LABELS

4-RL1C-06780 STARLIGHT WS AP903 WG74

Face Material

Natural embossed pearlescent white wet strength paper.

Type Embossed paper Colour and Finish Pearlescent white Weight 90 g/m 2 ±10% ISO-536 Thickness 110 μ ±10% ISO 534-80

Adhesive

Acrylic permanent adhesive featuring good clarity. Excellent adhesion on a wide variety of materials, including apolar substrates (like PE and PP). This adhesive can be used on slightly rough surfaces.

Reference AP903

Type Acrylic permanent

Min. Appl. Temp. -5°C

Service Temp. -40°C/+120°C

Shear Low

Tack 8 N/25mm FINAT FTM9 Final Adhesion 9 N/25mm FINAT FTM2

This adhesive is approved by ISEGA (Direct contact dry, moist and such kind of fatty foodstuffs which have a correction factor of at least 2 according to Annex III, Table 2 of the Regulation (EU) No. 10/2011), according to the German Recommendations XIV and complies with FDA 175.105.

Liner

Type One side siliconised Glassine

Colour and Finish White

Weight 72 g/m² ±10% PP-032 - ISO 536

Thickness 63 μ ±10% ISO 534 Transparency >40 % DIN 53 147-64

Applications

For production of high quality labels for beverages, wine and promotional uses.

Especially recommended for wine bottles requiring ice bucket immersion.

Not recommended for neck labels and small diameter bottles.

REELS MUST BE WOUND WITH THE FACE-SIDE OUT.

Printing Methods

Printable with letterpress, flexo, offset and hot foil. Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of $22^{\circ}\text{C} \pm 2^{\circ}\text{C}$ and 50 \pm 5% of Relative Humidity.
- · Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.

All information is subject to change without prior notice.





