

description

Uncoated premium quality papers and boards made with E.C.F. pulp, FSC® certified, felt-marked on both sides. Exceptional look-through and clarity. Available in Gesso shade.

The special Touch Class[®] treatment ensures resistance to fingerprints, varnishes, oils and water and, on the one hand, ensures perfect printing results with digital varnishes and foils (Scodix® technology and similar). On the other hand, it allows use in applications requiring high resistance to handling, such as printing menus in the catering sector. Soho Tintoretto Touch Class[®] can be printed in offset UV, digital dry toner and HP Indigo technology.

range

size	grain	substance	
32x46,4	LG	95	
33x48 , 2	LG	95	
46,4x32	SG	200	300
48,2x33	SG	200	300
72x52	SG	95	
52x72	LG	200	300

technical features ref. standard/instrument unit of measure

substance	thickness	Taber stiffness 15°		tensile strength	
ISO 536	ISO 534	ISO 2493		ISO 1924	
g/m²	μm	mN		kN/m	
	± 5%	long±10%	trasv±10%	long±10%	trasv±10%
95 ± 3%	130	7	3	6,5	3,3
200 ± 4%	275	85	37	10	4,8
300 ± 5%	430	245	110	13	7

Brightness (col. Gesso) - ISO 2470 (R457) - 99% ± 2 Relative Humidity 50% ± 5 ref. TAPPI 502-98

ecological features









The mark of

notes

The product is completely biodegradable and recyclable. Special runs available upon request. Depending on the type of toner (liquid or dry from different manifacturers), and independently from the kind of paper in use, we recomment to run preliminary tests and possibly verify with the machine supplier which is the most suitable serie of varnish to run the job.

The Company reserves the right to modify the technological features of the product in relation to market requirements.

